



NOTE: Canopy may be changed

NOTE: Canopy may be changed

LxBxH 8.00 x 2.85 x 3.10m
CAPACITY

SHIP NAME
PORT OF REGISTRY

ELEVATION

REAR/FRONT VIEW

PLAN (BOAT ON PORT SIDE SHOWN)

CALL SIGN

MAIN PARTICULARS

| | |
|-------------------|----------------------|
| LENGTH (MOULDED) | 8.00M |
| BREADTH (MOULDED) | 2.85M |
| DEPTH | 1.20M |
| HEIGHT | 3.10M |
| HOOK DIST | 7.60M |
| HOOK TYPE | NADIRO DIB 75 |
| NO. OF PERSON | 62P |
| CRAFT WEIGHT | 3885KG |
| SPEED | >6 KNOTS |
| TOTAL WEIGHT | 9000KG (82.5Kg/pers) |
| ENGINE | 380J-3 |

| 48 | Hydraulic pump or tank | 1 | | | | |
|-----|-----------------------------|-------------------------|------------------------------|---------------------------|-------|------|
| 47 | Pilot controlled valve | 1 | | | | |
| 46 | Accumulator | 1 | | | | |
| 45 | Emergency release valve | 1 | | | | |
| 44 | Operation panel | 1 | | | | |
| 43 | Plug for charging | 1 | | | | |
| 42 | Vent for batteries | 1 | | | | |
| 41 | Water sensor unit | 1 | | | | |
| 40 | Release unit | 1 | | | | |
| 39 | Rain collection | 1 | | | | |
| 38 | | | | | | |
| 37 | Emergency steering handle | 1 | Hot dipped galvanized steel | | | |
| 36 | Skate | 2 | Rubber & aluminium plate | | | |
| 35 | Rail | 2 | | | | |
| 34 | Food compartment | 1 | | | | |
| 33 | Oar/crutch | 2 | Wood | | | |
| 32 | Water compartment | 3 | G.R.P | | | |
| 31 | Steering gear | 1 | | | | |
| 30 | Engine & propeller shaft | 1 | | | | |
| 29 | Steering nozzle & propeller | 1 | F.R.P. / NiMn-Bronze Cu3-Cu4 | | | |
| 28 | Batteries | 2 | | | | |
| 27 | Axe | 2 | | | | |
| 26 | Pillar | 1 | G.R.P | | | |
| 25 | | | | | | |
| 24 | Drain plug | 1 | | | | |
| 23 | Manual pump | 1 | | | | |
| 22 | Fire extinguisher | 1 | | | | |
| 21 | Fuel tank | 1 | | | | |
| 20 | | | | | | |
| 19 | Safety belt | 1/per. | | | | |
| 18 | Equipment compartment | 2 | | | | |
| 17 | Door latch | 1 lot | AlSI 316L | | | |
| 16 | Back rest | 1 | Plywood | | | |
| 15 | Control panel | 1 | G.R.P | | | |
| 14 | Search light | 1 | | | | |
| 13 | INT. light | 2 | | | | |
| 12 | Helmsman chair | 1 | G.R.P | | | |
| 11 | Painter release hook | 1 | Hot dipped galvanized steel | | | |
| 10 | Gripping bobbin | 2 | Hot dipped galvanized steel | | | |
| 9 | Hook device arrangement | 2 | Nadiro DIB 75 | | | |
| 8 | Life line | 2 | PVC shield wire rope | | | |
| 7 | Remote control line hole | 1 | | | | |
| 6 | Door, window & hatch | 1 lot | | | | |
| 5 | Bollard | 1 | AlSI 316L | | | |
| 4 | Reflect light strip | 1 | | | | |
| 3 | Ventilator | 1 | | | | |
| 2 | Position light | 1 | | | | |
| 1 | Radar reflector | 1 | | | | |
| NO. | REF DWG NO. | DESCRIPTION | QTY | REMARKS | | |
| 1 | | USE NEW TEMPLATE | | KARL PHLI THWA 17.06.2019 | | |
| 0 | | ISSUED FOR CONSTRUCTION | | KARL PHLI THWA 16.04.2019 | | |
| REV | | DESCRIPTION | BY | CHECK | APPRO | DATE |

REVISION HISTORY



VIKING NORSAFE

VIKING Norsafe Life-Saving Equipment Norway AS
P.O Box 115 Tel: +47 37 05 85 00
4852 Færvik Fax: +47 37 05 85 01
NORWAY 24/7 Service: +47 37 05 63 33
Email: viking@viking-life.com

This drawing is the sole property of VIKING Norsafe Life-Saving Equipment Norway AS. It must not be submitted to other parties nor used in any manner detrimental to our interests. It shall not be copied, reproduced, used for manufacturing or sale without the written consent of VIKING Norsafe Life-Saving Equipment Norway AS. All rights are reserved.

| | | | | | |
|---------------------------------------|--------------------|----------------------|----------|---------|------------|
| DWG SIZE: A3 | SCALE: 1:30 | COPY OF: | PART NO. | WEIGHT: | SHEET: 1/1 |
| CLIENT NO: | PROJECTION METHOD: | EXTERNAL ARRANGEMENT | | | |
| TOLERANCES: ISO 2768-mk, ISO 13920-BF | REVISION: 1 | NADIRO DIB 75 | | | |
| DWG No: G-503143 | PROJECT: STANDARD | JYN-80DC | | | |
| | | GENERAL | | | |

Due to manufacturing reasons dimensions may vary up to 50mm